



Separate outer ring, integral inner ring

(Unit) : mm

Model	Dimensions						Basic rated load (kN)				Weight Kg	Corresponding model INA
	Inner ring	Outer ring	Width	Pitch ring	Shoulder diameter		Axial		Radial			
	d	D	B	Dpw	ds	Dh	Ca	Coa	Cr	Cor		
JRC 7010	70	90	10	80	79.5	80.5	18	60	12	30	0.3	SX011814
JRC 9013	90	115	13	102	101.5	102.5	26	96	17	47	0.4	SX011818
JRC 10013	100	125	13	112	111.5	112.5	28	106	18	52	0.5	SX011820
JRC 12016	120	150	16	135	134.4	135.6	41	153	26	75	0.8	SX011824
JRC 14018	140	175	18	157	156.3	157.7	64	237	41	116	1.1	SX011828
JRC 16020	160	200	20	180	179.2	180.8	69	272	44	133	1.7	SX011832
JRC 18022	180	225	22	202	201.2	202.8	98	381	63	187	2.3	SX011836
JRC 20024	200	250	24	225	224.2	225.8	106	425	68	208	3.1	SX011840
JRC 24028	240	300	28	270	269.2	270.8	149	612	95	300	5.3	SX011848
JRC 30038	300	380	38	340	339.2	340.8	245	1027	156	504	12	SX011860
JRC 34038	340	420	38	380	379.2	380.8	265	1148	167	363	13.5	SX011868
JRC 40046	400	500	46	450	449	451	385	1699	244	833	24	SX011880
JRC 50056	500	620	56	560	558.8	561.2	560	2538	355	1244	44	SX0118/500